

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **08263988 A**

(43) Date of publication of application: **11.10.96**

(51) Int. Cl. **G11C 14/00**
G11C 11/22
H01L 27/10
H01L 21/8247
H01L 29/788
H01L 29/792

(21) Application number: **07064317**

(71) Applicant: **SONY CORP**

(22) Date of filing: **23.03.95**

(72) Inventor: **EMORI TAKAYUKI**

(54) **FERROELECTRIC MEMORY**

(57) Abstract:

PURPOSE: To obtain a ferroelectric memory which can surely perform erasure- blocking operation for a non-selection cell in data erasing operation.

CONSTITUTION: A gate oxide film 5, the lower part electrode 4, a ferroelectric film 3, and the upper part electrode 2 are formed in this order in a channel region formed between a source 6 and a drain 7. In data erasing operation, voltage 0V is impressed to a silicon substrate 8 continuously. Negative voltage '-Vpp' is impressed to the upper part electrode 2 of a selection cell with the prescribed fall timing, thereby, the ferroelectric film 3 is polarized in the prescribed one side direction, and memory data is erased. Voltage 0V is continuously impressed to the upper part electrode 2 of a non-selection cell, and a polarization state of the ferroelectric film 3 is held as it is.

COPYRIGHT: (C)1996,JPO

